



JIS B2401 O型圈 G番 规格表1
(用于运动、圆筒面固定、平面固定)



JIS 编号称呼	O型圈尺寸	
	线径d2	内径d1
*G 3	3.1±0.1	2.4 ±0.14
*G 4		3.4 ±0.14
*G 5		4.4 ±0.15
*G 6		5.4 ±0.15
*G 7		6.4 ±0.16
*G 8		7.4 ±0.16
*G 9		8.4 ±0.17
*G 10		9.4 ±0.17
*G 11		10.4 ±0.18
*G 12		11.4 ±0.18
*G 13		12.4 ±0.19
*G 14		13.4 ±0.19
*G 15		14.4 ±0.20
*G 16		15.4 ±0.20
*G 17		16.4 ±0.21
*G 18		17.4 ±0.21
*G 19		18.4 ±0.22
*G 20		19.4 ±0.22
*G 21		20.4 ±0.23
*G 22		21.4 ±0.24
*G 23		22.4 ±0.24
*G 24		23.4 ±0.24
G 25		24.4 ±0.25
G 30		29.4 ±0.29
G 35		34.4 ±0.33
G 40		39.4 ±0.37
G 45		44.4 ±0.41
G 50		49.4 ±0.45
*G 52		51.4 ±0.47
G 55		54.4 ±0.49
*G 58		57.4 ±0.51
G 60		59.4 ±0.53
*G 62		61.4 ±0.54
*G 63		62.4 ±0.55
*G 64		63.4 ±0.56
G 65		64.4 ±0.57
*G 67		66.4 ±0.59
G 70		69.4 ±0.61
*G 72		71.4 ±0.63
G 75		74.4 ±0.65
G 80		79.4 ±0.69
G 85		84.4 ±0.73
G 90		89.4 ±0.77
G 95		94.4 ±0.81
G 100		99.4 ±0.85
G 105		104.4 ±0.87
G 110		109.4 ±0.91
G 115	114.4 ±0.94	
G 120	119.4 ±0.98	
G 125	124.4 ±1.01	
G 130	129.4 ±1.05	
G 135	134.4 ±1.08	
G 140	139.4 ±1.12	
G 145	144.4 ±1.16	
*G s150	149.3 ±1.19	
*G s155	154.3 ±1.23	

JIS 编号称呼	O型圈尺寸	
	线径d2	内径d1
*Gs 160	3.1±0.1	159.3 ±1.26
*Gs 165		164.3 ±1.30
*Gs 170		169.3 ±1.33
*Gs 175		174.3 ±1.37
*Gs 180		179.3 ±1.40
*Gs 185		184.3 ±1.44
*Gs 190		189.3 ±1.47
*Gs 195		194.3 ±1.51
*Gs 200		199.3 ±1.55
*Gs 205		204.3 ±1.58
*Gs 210		209.3 ±1.61
*Gs 215		214.3 ±1.65
*Gs 220		219.3 ±1.68
*Gs 225		224.3 ±1.71
*Gs 230		229.3 ±1.75
*Gs 235		234.3 ±1.78
*Gs 240		239.3 ±1.81
*Gs 245		244.3 ±1.85
*Gs 250		249.3 ±1.88
*Gs 255		254.3 ±1.91
*Gs 260		259.3 ±1.94
*Gs 265		264.3 ±1.98
*Gs 270		269.3 ±2.01
*Gs 275		274.3 ±2.04
*Gs 280		279.3 ±2.07
*Gs 285		284.3 ±2.11
*Gs 290		289.3 ±2.14
*Gs 295		294.3 ±2.17
*Gs 300		299.3 ±2.20
*Gs 305		304.3 ±2.24
*Gs 310		309.3 ±2.27
*Gs 315		314.3 ±2.30
*Gs 320		319.3 ±2.33
*Gs 325		324.3 ±2.36
*Gs 330		329.3 ±2.39
*Gs 335		334.3 ±2.42
*Gs 340		339.3 ±2.45
*Gs 345		344.3 ±2.48
*Gs 350		349.3 ±2.51
*Gs 355		354.3 ±2.54
*Gs 360		359.3 ±2.57
*Gs 365		364.3 ±2.60
*Gs 370		369.3 ±2.63
*Gs 375		374.3 ±2.67
*Gs 380		379.3 ±2.70
*Gs 385		384.3 ±2.73
*Gs 390		389.3 ±2.77
*Gs 395	394.3 ±2.79	
*Gs 400	399.3 ±2.82	
*Gs 405	404.3	±3.00
*Gs 410	409.3	
*Gs 415	414.3	
*Gs 420	419.3	
*Gs 425	424.3	
*Gs 430	429.3	
*Gs 435	434.3	


JIS B2401 O型圈 G番 规格表2
(用于运动、圆筒面固定、平面固定)



JIS 编号称呼	O型圈尺寸	
	线径 d ₂	内径 d ₁
*Gs 440	3.1 ± 0.12	439.3
*Gs 445		444.3
*Gs 450		449.3
*Gs 455		454.3
*Gs 460		459.3
*Gs 465		464.3
*Gs 470		469.3
*Gs 475		474.3
*Gs 480		479.3
*Gs 485		484.3
*Gs 490		489.3
*Gs 495		494.3
*Gs 500		499.3
G 150		5.7 ± 0.13
G 155	154.3	
G 160	159.3	
G 165	164.3	
G 170	169.3	
G 175	174.3	
G 180	179.3	
G 185	184.3	
G 190	189.3	
G 195	194.3	
G 200	199.3	
*G 205	204.3	
G 210	209.3	
*G 215	214.3	
G 220	219.3	
*G 225	224.3	
G 230	229.3	
*G 235	234.3	
G 240	239.3	
*G 245	244.3	
G 250	249.3	
*G 255	254.3	
G 260	259.3	
*G 265	264.3	
G 270	269.3	
*G 275	274.3	
G 280	279.3	
*G 285	284.3	
G 290	289.3	
*G 295	294.3	
G 300	299.3	
*G 305	304.3	

JIS 编号称呼	O型圈尺寸	
	线径 d ₂	内径 d ₁
*G 310	5.7 ± 0.13	309.3
*G 315		314.3
*G 320		319.3
*G 325		324.3
*G 330		329.3
*G 335		334.3
*G 340		339.3
*G 345		344.3
*G 350		349.3
*G 355		354.3
*G 360		359.3
*G 365		364.3
*G 370		369.3
*G 375		374.3
*G 380	379.3	
*G 385	384.3	
*G 390	389.3	
*G 395	394.3	
*G 400	399.3	
*G 405	5.7 ± 0.15	404.3
*G 410		409.3
*G 415		414.3
*G 420		419.3
*G 425		424.3
*G 430		429.3
*G 435		434.3
*G 440		439.3
*G 445		444.3
*G 450		449.3
*G 455		454.3
*G 460		459.3
*G 465		464.3
*G 470		469.3
*G 475	474.3	
*G 480	479.3	
*G 485	484.8	
*G 490	489.3	
*G 495	494.3	
*G 500	499.3	
*G 505	504.3	
*G 510	509.3	
*G 515	514.3	
*G 520	519.3	
*G 525	524.3	
*G 530	529.3	

JIS B2401 O型圈 G番 规格表3
(用于运动、圆筒面固定、平面固定)



JIS	O型圈尺寸	
编号称呼	线径 d ₂	内径 d ₁
*G 535	5.7 ± 0.15	534.3
*G 540		539.3
*G 545		544.3
*G 550		549.3
*G 555		554.3
*G 560		559.3
*G 565		564.3
*G 570		569.3
*G 575		574.3
*G 580		579.3
*G 585		584.3
*G 590		589.3
*G 595		594.3
*G 600		599.3
*G 610		609.3
*G 620		319.3
*G 630		629.3
*G 640		639.3
*G 650		649.3
*G 660		659.3
*G 670		669.3
*G 680		679.3
*G 690		689.3
*G 700		699.3
*G 710		709.3
*G 720		719.3
*G 730		729.3
*G 740		739.3
*G 750		749.3
*G 760		759.3
*G 770	769.3	
*G 780	779.3	
*G 790	789.3	
*G 800	799.3	
*G 810	809.3	
*G 820	819.3	
*G 830	829.3	
*G 840	839.3	
*G 850	849.3	
*G 860	859.3	
*G 870	869.3	
*G 880	879.3	
*G 890	889.3	
*G 900	899.3	
*G 910	909.3	

JIS	O型圈尺寸	
编号称呼	线径 d ₂	内径 d ₁
*G 920	5.7 ± 0.15	919.3
*G 930		929.3
*G 940		939.3
*G 950		949.3
*G 960		959.3
*G 970		969.3
*G 980		979.3
*G 990		989.3
*G 1000		999.3
*G 1020		1019.3
*G 1040		1039.3
*G 1060		1059.3
*G 1080		1079.3
*G 1100		1099.3
*G 1120		1119.3
*G 1140		1139.3
*G 1160		1159.3
*G 1180		1179.3
*G 1200		1199.3
*G 1220		1219.3
*G 1240		1239.3
*G 1260		1259.3
*G 1280		1279.3
*G 1300		1299.3
*G 1320		1319.3
*G 1340		1339.3
*G 1360		1359.3
*G 1380		1379.3
*G 1400		1399.3
*G 1420		1419.3
*G 1440	1439.3	
*G 1460	1459.3	
*G 1480	1479.3	
*G 1500	1499.3	