

HLB-轴承用



规格表 (M10~M200)

型号	称呼	节距	凸螺母					凹螺母					①、②通用		组合高度	与底面垂直度	锁紧扭矩 (N.m) (强度通用) 凹螺母		
			D		B1		b	D1		D2	B		S	g				f	Max
			尺寸	公差	尺寸	公差		尺寸	公差	尺寸	尺寸	公差							
HLB-00	M10	0.75	18	0 -0.5	6	0 -0.5	3.5	18	0 -0.5	17	6	0 -0.5	3	14	9.5	0.05	16		
HLB-01	M12	1	22	0 -0.5	6	0 -0.5	3.5	22	0 -0.5	17	6	0 -0.5	3	18	9.5		16		
HLB-02	M15	1	25	0 -0.5	7	0 -0.5	4.5	25	0 -0.5	21	7	0 -0.5	4	21	11.5		28		
HLB-03	M17	1	28	0 -0.5	7	0 -0.5	4.5	28	0 -0.5	24	7	0 -0.5	4	24	11.5		37		
HLB-04	M20	1	32	0 -0.5	8	0 -0.5	5.5	32	0 -0.5	26	8	0 -0.5	4	28	13.5		55		
HLB-05	M25	1.5	38	0 -0.5	10	0 -0.5	6	38	0 -0.5	32	10	0 -0.5	5	34	16		80		
HLB-06	M30	1.5	45	0 -0.5	10	0 -0.5	6	45	0 -0.5	38	10	0 -0.5	5	41	16		115		
HLB-07	M35	1.5	52	0 -0.5	11	0 -0.5	7	52	0 -0.5	44	11	0 -0.5	5	48	18		130		
HLB-08	M40	1.5	58	0 -0.5	9	0 -0.5	5	58	0 -0.5	50	12	0 -0.5	6	53	17		155		
HLB-09	M45	1.5	65	0 -0.5	10	0 -0.5	6	65	0 -0.5	56	13	0 -0.5	6	60	19		170		
HLB-10	M50	1.5	70	0 -0.5	11	0 -0.5	7	70	0 -0.5	61	14	0 -0.5	6	65	21	200			
HLB-11	M55	2	75	0 -0.5	11	0 -0.5	6	75	0 -0.5	67	15	0 -0.5	7	69	21	0.07	210		
HLB-12	M60	2	80	0 -0.5	11	0 -0.5	6	80	0 -0.5	73	15	0 -0.5	7	74	21		240		
HLB-13	M65	2	85	0 -0.5	12	0 -0.5	7	85	0 -0.5	79	12	0 -0.5	7	79	19		255		
HLB-14	M70	2	92	0 -0.5	12	0 -0.5	7	92	0 -0.5	85	12	0 -0.5	8	85	19		270		
HLB-15	M75	2	98	0 -0.5	13	0 -0.5	8	98	0 -0.5	90	13	0 -0.5	8	91	21		300		
HLB-16	M80	2	105	0 -0.5	15	0 -0.5	10	105	0 -0.5	95	15	0 -0.5	8	98	25		310		
HLB-17	M85	2	110	0 -0.5	16	0 -0.5	11	110	0 -0.5	102	16	0 -0.5	8	103	27		340		
HLB-18	M90	2	120	0 -0.5	16	0 -0.5	11	120	0 -0.5	108	16	0 -0.5	10	112	27		350		
HLB-19	M95	2	125	0 -0.5	17	0 -0.5	12	125	0 -0.5	113	17	0 -0.5	10	117	29		380		
HLB-20	M100	2	130	0 -0.5	18	0 -0.5	13	130	0 -0.5	120	18	0 -0.5	10	122	31		390		
HLB-21	M105	2	140	0 -0.5	18	0 -0.5	12	140	0 -0.5	126	18	0 -0.5	12	130	30	410			
HLB-22	M110	2	145	0 -0.5	19	0 -0.5	13	145	0 -0.5	133	19	0 -0.5	12	135	32	415			
HLB-23	M115	2	150	0 -0.5	19	0 -0.5	13	150	0 -0.5	137	19	0 -0.5	12	140	32	420			
HLB-24	M120	2	155	0 -0.5	20	0 -0.5	13	155	0 -0.5	138	20	0 -0.5	12	145	33	435			
HLB-25	M125	2	160	0 -0.5	21	0 -0.7	14	160	0 -0.5	148	21	0 -0.7	12	150	35	440			
HLB-26	M130	2	165	0 -0.5	21	0 -0.7	14	165	0 -0.5	149	21	0 -0.7	12	155	35	450			
HLB-27	M135	2	175	0 -0.5	22	0 -0.7	15	175	0 -0.5	160	22	0 -0.7	14	163	37	455			
HLB-28	M140	2	180	0 -0.5	22	0 -0.7	15	180	0 -0.5	160	22	0 -0.7	14	168	37	465			
HLB-29	M145	2	190	0 -0.5	24	0 -0.7	16	190	0 -0.5	171	24	0 -0.7	14	178	40	0.1	470		
HLB-30	M150	2	195	0 -0.5	24	0 -0.7	16	195	0 -0.5	171	24	0 -0.7	14	183	40		480		
HLB-31	M155	3	200	0 -0.5	25	0 -0.7	17	200	0 -0.5	182	25	0 -0.7	16	186	42		485		
HLB-32	M160	3	210	0 -0.5	25	0 -0.7	17	210	0 -0.5	182	25	0 -0.7	16	196	42		500		
HLB-33	M165	3	210	0 -0.5	26	0 -0.7	17	210	0 -0.5	193	26	0 -0.7	16	196	43		550		
HLB-34	M170	3	220	0 -0.5	26	0 -0.7	17	220	0 -0.5	193	26	0 -0.7	16	206	43		600		
HLB-36	M180	3	230	0 -0.5	27	0 -0.7	18	230	0 -0.5	203	27	0 -0.7	18	214	45		700		
HLB-38	M190	3	240	0 -0.5	28	0 -0.7	19	240	0 -0.5	214	28	0 -0.7	18	224	47		800		
HLB-40	M200	3	250	0 -0.5	29	0 -0.7	20	250	0 -0.5	226	29	0 -0.7	18	234	49		900		